

REDWING®

DRIVEN BY SUPERIOR STRENGTH, QUALITY AND VALUE

HEAVY DUTY TYRE SEALANT

Maximise uptime by
reducing the risk of
punctures across
your machinery fleet

- ✓ Continuous protection against flat tyres
- ✓ Reduce fuel costs by maintaining correct tyre pressure
- ✓ Suitable for on-road highway truck tyres and all pneumatic off-road applications - including tractors, forklifts, excavators, mowers and all-terrain vehicles
- ✓ Water-soluble gel - containing rubber crumb for maximum effect. Can be washed out with water, using normal tap pressure
- ✓ Environmentally friendly - non-hazardous, non-flammable and non-toxic
- ✓ Harmless to tyre and rim
- ✓ Manufactured in the UK

Comes in flexi packs or drums:

Flexi Pack (1l) Spout nozzle fits over the tyre valve stem.

Drums (20 litres) to be used with a tyre sealant application pump

Quantity used is according to tyre size

www.redstoneuk.com

Due to the ever-increasing demands from vehicle operators on their vehicle tyres, the market is constantly looking for ways of reducing the downtime caused by punctures and getting maximum life from their tyres.

Tyre sealant is becoming increasingly recognised across industries and fleets as the ideal solution to dealing with punctures cost effectively.

With the Redwing Heavy Duty Tyre Sealant, the cost of protecting a four-wheeled vehicle is considerably less than replacing a single tyre.



Redwing Heavy Duty Tyre Sealant seals the puncture as it happens, ensuring the vehicle can continue to operate as normal. Under inflated tyres have an impact on the vehicle's fuel consumption, due to increased rolling resistance generated by additional heat build up within the tyre. Easy to apply, anywhere on site without specialist tools or knowledge!

How to use it. Park machine with valve at the top of the tyre and remove valve core, using a valve core tool. Attach nozzle of pump (or spout if using Flexi Pack) and pump in the required amount of sealant into the tyre. One pump of the handle inserts 100ml of sealant. Remove nozzle, insert valve core and reinflate tyre to the correct pressure. Tyres containing Redwing sealant can be removed from the wheel in the normal way and repaired to the industry standards, should a permanent repair be required.

REDWING®

DRIVEN BY SUPERIOR STRENGTH, QUALITY AND VALUE

Application Chart



SIZE	LITRE	SIZE	LITRE	SIZE	LITRE	SIZE	LITRE
4 Inch		14 Inch		20 Inch		30 Inch	
9x3.50-4	0.65	27x9.00R14	1.75	9.00-20	3.50	420/70R30	8.00
11x4.00-4	0.65	27x11.00R14	2.00	10.00-20	3.50	16.9R30	9.25
5 Inch		185R14	1.50	11.00-20	4.00	480/70R30	9.50
11x4.00-5	0.65	195R14	1.50	12.00-20	4.50	520/70R30	10.50
4.10/3.50-5	0.65	205R14	1.75	41x14.00-20	5.00	30.5 Inch	
6 Inch		15 Inch		16.0/70-20	6.25	650/65-30.5	12.5
13x5.00-6	0.90	8.25-15	2.00	22.5 Inch		32 Inch	
145/70-6	0.90	27x8.50-15	1.75	500/60-22.5	7.50	12.4R32	6.00
13x6.50-6	0.90	29x12.50-15	2.75	500/60-22.5	7.50	24.5-32	15.00
15x6.00-6	0.90	31x13.50-15	3.25	24 Inch		650/75R32	15.50
8 Inch		33x12.50-15	3.00	8.3-24	4.00	30.5R32	16.00
4.80/4.00-8	0.90	36x13.50-15	3.50	11.2-24	5.00	34 Inch	
16x6.50-8	1.00	15.3 Inch		12.00-24	5.25	16.9R34	9.25
16x7.50-8	1.00	10.0/75-15.3	3.50	12.4/11-24	5.50	18.4R34	10.00
18x8.50-8	1.50	11.5/80-15.3	3.50	13.6R24	5.75	480/70R34	10.00
18x9.50-8	1.50	12.5/80-15.3	4.00	360/70R24	5.75	23.1-34	13.50
20x10.00-8	1.50	16 Inch		420/70R24	7.00	36 Inch	
22x11.00-8	2.00	6.00-16	2.00	15.5/80-24	7.25	12.4R36	6.25
9 Inch		6.50-16	2.50	16.9R24	7.50	13.6R36	7.50
20x10.00-9	1.50	7.50-16	2.00	17.5-24	8.00	38 Inch	
22x11.00-9	2.00	9.00-16	3.00	460/70-24	8.00	12.4-38	6.50
25x12.00-9	2.00	9.50-16	3.00	19.5-24	8.75	13.6R38	7.00
10 Inch		10.00-16	3.50	25 Inch		14.9R38	7.00
7.50-10	1.60	10.5/65-16	3.00	15.25R25	7.25	16.9R38	9.75
18x8.50-10	1.50	13.6-16	4.00	17.5R25	8.50	480/70R38	10.50
20x10.00-10	1.75	16.50-16	5.50	26.5-25	14.00	18.4R38	11.50
20x12.00-10	1.75	16.5 Inch		26 Inch		520/70R38	12.00
22x11.00-10	1.75	10-16.5	3.50	480/70R26	8.75	20.8R38	12.50
24x12.00-10	2.50	12-16.5	4.50	18.4-26	9.25	580/70R38	13.75
12 Inch		17 Inch		23.1-26	12.50	16.9R42	10.00
5.00-12	1.00	15.0/55-17	4.50	620/75-26	12.50	20.8R42	13.50
6.00-12	1.00	19.0/45-17	5.50	28.1-26	15.00	42 Inch	
7.00-12	1.75	18 Inch		28 Inch		16.9R42	10.00
23x10.50-12	2.00	10.5/80-18	3.50	11.2-28	5.50	20.8R42	13.50
24x12.00-12	2.00	12.5/80-18	4.00	13.6-28	6.00	46 Inch	
24x13.00-12	2.25	15.0/70-18	5.00	14.9R28	6.75	12.4R46	7.25
25x8.00-12	1.75	19 Inch		380/70R28	6.75	51 Inch	
25x10.00-12	2.00	6.00-19	2.50	420/70R28	7.50	33.00-51	28.00
26x12.00-12	2.25	7.00-19	2.75	16.9R28	8.00	36.00-51	35.00
				18.4-28	9.50		

Size missing? Work out volume by using the following formula:

Tyre height x tyre width (inches) = x 3.14 = multiply by 0.0018 = litres per wheel



Redstone (Tyres) Ltd
South Yard, Ford Lane, Arundel
West Sussex BN18 0DF



Place your order on **01243 558959**
or email **sales@redstoneuk.com**
visit **www.redstoneuk.com**