TYRE TECHNICAL SHEET

TURF24 RX ARAMID

16x6.50-8 RX Aramid 6PR



Tyre Information	
Tyre size	16x6.50-8
Product code	01/08/16650/TK6/RWT24X1
Tread pattern	Turf 24
Ply rating	6

Dimensional Data	
Mounted diameter (mm)	412
Mounted width (mm)	167
Rim width (inch)	5.375
Rim diameter (inch)	8
Tyre weight (kg)	3.6
Tread depth (mm)	5

Inflation and Load Data	
Rated pressure (PSI)	42
Rated load (kg)	368
Rated speed	-

Performance Data	
Rolling circ. (mm)	-
Static load radius (mm)	-
Deflection	-

+/- 5%

Not suitable for highway use

REDWING®

DRIVEN BY SUPERIOR STRENGTH, QUALITY AND VALUE

Advanced engineering

- ✓ Thick shoulder rubber gives class-leading puncture resistance
- ✓ Shallow tread and rounded shoulders to minimise marking
- ✓ Built using the most robust carcass in its class
- ✓ RX Aramid - superior puncture resistance

Richard Hull | Tecnical Director

R. A. Hull



REDSTONE

W: **01243 558959**
E: **sales@redstoneuk.com**
W: **www.redstoneuk.com**