

# TYRE TECHNICAL SHEET

## TURF24

### 23x10.50-12 RX Aramid 6PR



Tyre Information	
Tyre size	23x10.50-12
Product code	01/12/231050/T4/RWT241
Tread pattern	Turf 24
Ply rating	6

Dimensional Data	
Mounted diameter (mm)	557
Mounted width (mm)	248
Rim width (inch)	8.5
Rim diameter (inch)	12
Tyre weight (kg)	9
Tread depth (mm)	7

Inflation and Load Data	
Rated pressure (PSI)	32
Rated load (kg)	800
Rated speed	-

Performance Data	
Rolling circ. (mm)	-
Static load radius (mm)	-
Deflection	-

+/- 5%

Not suitable for highway use

**REDWING**<sup>®</sup>  
DRIVEN BY SUPERIOR STRENGTH, QUALITY AND VALUE

#### Advanced engineering

- ✓ Thick shoulder rubber gives class-leading puncture resistance
- ✓ Shallow tread and rounded shoulders to minimise marking
- ✓ Built using the most robust carcass in its class
- ✓ RX Aramid - superior puncture resistance

Richard Hull | Technical Director



W: 01243 558959  
E: [sales@redstoneuk.com](mailto:sales@redstoneuk.com)  
W: [www.redstoneuk.com](http://www.redstoneuk.com)

