

TYRE TECHNICAL SHEET

TURF24

24x12.00-12 6PR



Tyre Information

| | |
|---------------|------------------------|
| Tyre size | 24x12.00-12 |
| Product code | 01/12/241200/T6/RWT241 |
| Tread pattern | Turf 24 |
| Ply rating | 6 |

Dimensional Data

| | |
|-----------------------|------|
| Mounted diameter (mm) | 583 |
| Mounted width (mm) | 257 |
| Rim width (inch) | 10.5 |
| Rim diameter (inch) | 12 |
| Tyre weight (kg) | 10 |
| Tread depth (mm) | 8 |

Inflation and Load Data

| | |
|----------------------|------|
| Rated pressure (PSI) | 32 |
| Rated load (kg) | 1030 |
| Rated speed | - |

Performance Data

| | |
|-------------------------|---|
| Rolling circ. (mm) | - |
| Static load radius (mm) | - |
| Deflection | - |

+/- 5%

Not suitable for highway use

REDWING®
DRIVEN BY SUPERIOR STRENGTH, QUALITY AND VALUE

Advanced engineering

- ✓ Thick shoulder rubber gives class-leading puncture resistance
- ✓ Shallow tread and rounded shoulders to minimise marking
- ✓ Built using the most robust carcass in its class

Richard Hull | Technical Director

R. A. Hull



W: 01243 558959
E: sales@redstoneuk.com
W: www.redstoneuk.com

