

REDWING®

DRIVEN BY SUPERIOR STRENGTH, QUALITY AND VALUE

TYRE SEALANT

Deals with **puncture problems** without you knowing you've had them

- ✓ Continuous protection against flat tyres
- ✓ Helps eliminate rim leaks
- ✓ Seals punctures up to 10mm in all tyre sizes
- ✓ Permitted use up to 65mph
- ✓ Application chart provided for optimum amounts per tyre size
- ✓ Easy to clean out (water soluble)
- ✓ Frost (to -20°C) and rust inhibitor
- ✓ Harmless to tyre and rim

Comes in bottles or drums:

Bottles (1 litre) come complete with an applicator nozzle

Drums (25 litres) to be used with a tyre sealant application pump

Quantity used is according to tyre size

www.redstoneuk.com

You know as well as we do that tyres are constantly under threat from nails and screws, thorns, pieces of flint and glass. Punctures aren't just irritating, they're a costly interruption to your day.

The answer? Treat your tyres with Redwing Tyre Sealant and give them an added layer of protection – reducing valuable downtime, eliminating puncture repair costs and saving you time and money.



Redwing Tyre Sealant uses leading fibre-technology that, through a physical and chemical reaction, effectively plugs puncture holes from the inside out and for good. Easy to apply, this top quality sealant is used effectively to protect tyres around the world, from the biggest earthmovers to the smallest ride-on-mowers.

How to use it. The prescribed quantity of sealant is injected into the tyre via the valve stem and circulates around the tyre as it moves. When a puncture occurs, the tyre's air pressure forces the sealant into the hole, plugging it quickly and effectively, with no loss of air pressure.

REDWING®

DRIVEN BY SUPERIOR STRENGTH, QUALITY AND VALUE

Application Chart

TYRE SEALANT



SIZE	LITRE
4 Inch	
3.00-4	0.25
9x3.50-4	0.25
11x4.00-4	0.25
4.10/3.50-4	0.25
11x7.00-4	0.50
5 Inch	
11x4.00-5	0.25
4.00-5	0.25
4.10/3.50-5	0.25
6 Inch	
4.00-6	0.50
4.10/3.50-6	0.50
13x5.00-6	0.50
145/70-6	0.50
13x6.50-6	0.50
14x4.00-6	0.50
15x6.00-6	0.50
7 Inch	
3.50-7	0.50
4.00-7	0.50
8 Inch	
3.50-8	0.50
4.80/4.00-8	0.50
5.00-8	0.50
15x6.00-8	0.50
16x6.50-8	0.75
16.5x6.50-8	0.75
16x7.50-8	0.75
18x6.50-8	0.75
18x8.50-8	1.00
18x9.50-8	1.00
20x10.00-8	1.25
22x11.00-8	1.50
22.5x10.00-8	1.50
9 Inch	
6.00-9	0.75
18x7.00-9	0.75
20x10.00-9	1.25
22x11.00-9	1.50
25x12.00-9	1.50
25x13.00-9	1.75
10 Inch	
4.00-10	0.50
6.50-10	1.00
7.50-10	1.25
18x8.50-10	1.00
20x8.00-10	1.25
20x10.00-10	1.50
20x12.00-10	1.50
22x11.00-10	1.50
24x12.00-10	1.75
11 Inch	
23x8.00-11	1.50
24x8.00-11	1.50
24x9.00-11	1.75
24x10.00-11	1.75

SIZE	LITRE
12 Inch	
4.00-12	0.50
5.00-12	0.75
6.00-12	0.75
6.5/80-12	1.00
7.00-12	1.25
23x8.50-12	1.25
23x10.50-12	1.50
24x12.00-12	1.75
24x13.00-12	2.00
25x8.00-12	1.50
25x10.00-12	1.75
26x12.00-12	2.00
26.5x14.00-12	2.25
11.0/65-12	2.25
14 Inch	
5.00-14	0.75
7.00-14	1.00
25x8.50-14	1.50
27x9.00R14	1.50
27x11.00R14	1.75
165R14	1.00
185R14	1.25
195R14	1.25
205R14	1.50
14.5 Inch	
200/60-14.5	1.50
15 Inch	
4.00-15	0.50
5.00-15	0.75
7.00-15	1.25
6.5/80-15	1.00
7.50-15	1.50
8.25-15	1.75
27x8.50-15	1.50
9.00-15	1.50
28x9.00-15	1.50
10.00-15	2.25
10.50-15	1.75
12.00-15	2.25
29x12.50-15	2.50
12.50-15	2.50
12.5L-15	2.50
13.50-15	3.00
31x13.50-15	3.00
31x15.50-15	3.50
33x12.50-15	2.50
36x13.50-15	3.00
15.3 Inch	
10.0/75-15.3	2.00
11.5/80-15.3	2.25
12.5/80-15.3	2.75
16 Inch	
4.00-16	0.50
4.50-16	0.75
5.00-16	0.75
5.50-16	1.00
6.00-16	1.00
6.50-16	1.25
7-16	1.50
7.50-16	1.50
8-16	1.75

SIZE	LITRE
8.25-16	1.75
9.00-16	2.00
9.50-16	2.00
10.00-16	2.25
10.5/65-16	2.25
11L-16	2.50
11.2-16	2.50
13.0/75-16	3.00
13.6-16	3.00
14.0/65-16	3.25
16.50-16	4.00
16.5 Inch	
10-16.5	2.25
12-16.5	2.75
17 Inch	
15.0/55-17	3.25
19.0/45-17	4.25
17.5 Inch	
8R17.5	1.50
9.5R17.5	2.00
18 Inch	
7.50-18	1.50
8-18	1.75
10.5/80-18	2.50
12.5/80-18	3.00
15.0/70-18	3.75
19 Inch	
4.00-19	0.75
4.50-19	0.75
6.00-19	1.25
7.00-19	1.50
19.5 Inch	
18-19.5	5.00
265/70R19.5	6.00
20 Inch	
6.50-20	1.50
7.50-20	1.75
8.25-20	2.00
9.00-20	2.25
9.5-20	2.25
10.00-20	2.50
11.00-20	2.75
11.2-20	2.75
12.00-20	3.00
12.50-20	3.00
14.00-20	3.75
41x14.00-20	3.75
14.5-20	4.00
16.0/70-20	4.50
20.0/70-20	6.25
22.5 Inch	
10.00-22.5	2.50
12.00-22.5	3.00
11R22.5	3.00
275/75R22.5	4.00
355/50R22.5	4.50
385/65R22.5	4.75
385/55R22.5	4.75
18-22.5	4.75
500/60-22.5	4.75

SIZE	LITRE
24 Inch	
8.3-24	2.00
9.5-24	2.50
11.2-24	3.25
12.00-24	3.75
12.4/11-24	3.00
13.6R24	4.00
13.00-24	4.00
360/70R24	4.00
14.00-24	4.75
14.9R24	4.75
420/70R24	5.00
15.5/80-24	5.25
16.00-24	5.25
16.5/80-24	5.25
16.9R24	5.50
18.00-24	7.75
19.5-24	6.50
21-24	7.50
25 Inch	
13.00-25	4.00
14.00-25	4.75
15.25R25	5.25
17.5R25	6.25
18.00-25	6.50
21.00-25	9.50
23.5-25	10.00
26.5-25	12.00
29.5-25	14.00
26 Inch	
14.9-26	5.00
16.9-26	5.75
480/70R26	6.50
18.4-26	6.75
23.1-26	9.50
28.1-26	11.00
28 Inch	
11.2-28	3.50
13.6-28	4.50
360/70R28	4.50
14.9R28	4.75
380/70R28	4.75
420/70R28	5.50
16.5/85-28	5.75
16.9R28	5.75
480/70R28	6.75
18.4-28	7.00
29 Inch	
26.5-29	13.00
29.5-29	15.00
30 Inch	
420/70R30	5.75
16.9R30	6.50
480/70R30	7.00
520/70R30	7.75
23.1-30	10.00
32 Inch	
12.4R32	4.25
24.5-32	11.00
650/75R32	11.00
30.5R32	14.00
800/65R32	14.00

SIZE	LITRE
33 Inch	
18.00-33	7.25
34 Inch	
16.9R34	6.75
18.4R34	7.50
480/70R34	7.50
23.1-34	10.00
36 Inch	
8.3-36	2.75
9.5-36	3.25
11.2-36	4.00
12.4R36	4.50
13.6R36	5.25
38 Inch	
8.3-38	2.75
9.5-38	3.25
11.2-38	4.00
12.4-38	4.75
13.6R38	5.50
14.9R38	5.50
15.5-38	6.00
16.9R38	7.25
480/70R38	8.00
18.4R38	8.50
520/70R38	9.00
20.8R38	9.50
580/70R38	10.00
39 Inch	
33.5-39	21.00
37.5-39	25.00
40.5-39	27.00
42 Inch	
16.9R42	7.50
20.8R42	10.00
43 Inch	
24.00-43	15.00
44 Inch	
9.5-44	3.75
45 Inch	
45.00-45	29.00
46 Inch	
12.4R46	5.25
49 Inch	
18.00-49	11.00
21.00-49	13.00
24.00-49	15.00
27.00-49	19.00
51 Inch	
30.00-51	23.00
33.00-51	25.00
36.00-51	29.00
50.00-51	38.00
65.00-51	60.00
57 Inch	
37.00-57	32.00
40.00-57	38.00



Redstone (Tyres) Ltd
South Yard, Ford Lane, Arundel
West Sussex BN18 0DF



Place your order on **01243 558959** or email **sales@redstoneuk.com** visit **www.redstoneuk.com**